

SD700J

7" LCD MONITOR

True Flat
Widescreen 16:9

1024 x 600 Resolution
800 x 480 Resolution



OVERVIEW

- Interface: USB or VGA+HDMI dual signal input
- Pole type or solid stand or VESA 75*75 mm mounting
- White or black chassis
- USB interface provides a single-cable solution combines power, video, and touch
- Rear I/O ports for easy access



VESA 75 x 75 mm



Tilt Adjustable

SD700J 7" LCD MONITOR

SPECIFICATION

	SD700JH		SD700JR	
Display Size	7 inch (16:9)			
Interface	USB B_Type	VGA+HDMI+ DC	USB B_Type	VGA+HDMI+ DC
Resolution	1024x600		800 x 480	
Power Source	5V USB X 1	DC 12V Adapter (1500mA)	5V USB X 1	DC 12V Adapter (1500mA)
Power Consumption	5V / 490mA	12V / 300mA	5V / 490mA	12V / 300mA
Display Area	153.6(H) x 90.0(V) mm		154.08(H) x 85.92(V) mm	
Display Type	TFT-LCD (Digital-Panel)			
Backlight	LED			
White Luminance	250 cd/m2		450 cd/m2	
Response Time	25 ms			
Viewing Angle	150° (Horizontal)/145° (Vertical)		140° (Horizontal)/120° (Vertical)	
Temperature	0° C~40° C (Operating)			
Physical Dimension	206.0 (L) x 162.5 (W) x 32.5(D) mm (Monitor Only)			
EMC / Safty Standards	FCC, CE			

I/O TYPES

